



PRODUCT OVERVIEW

Technology	LED
Dimmable	3 Step dim switch
Mount	Hook/Chain suspension (Include chain 1M)
Housing	Die-cast aluminium
Diffuser	PC (Polycarbonate)
CCT	3 Step CCT switch (CW: 6500K, NW : 4000K, WW : 3000K)
Luminous efficacy (lm/W)	@3000K=130lm/W, @4000K=150lm/W, @6500K=140lm/W
Beam angle	90°
CRI (Ra)	80
Power factor (PF)	> 0.9
THD	<15%
Voltage (V)	AC 220-240V
IP protection	65
Surge protection	6KV (L/N-PG)
IK rating	IK08
Lamps	SMD LED
Life-Time	30,000 hrs
Ambient Temperature	-20°C to 45°C
Standard	TIS1955-2551

TECHNICAL

Model	Power (W)	Step Dim A/B/C (W)	Step CCT CW/NW/WW (K)	Lumen (@6500K) (lm)	AxH (mm)	Weight (Kg)
DACO DISC GC209 CCT LED 100W	100W	100/75/50	6500/4000/3000	14,000	257x152	1.74
DACO DISC GC209 CCT LED 150W	150W	150/112/75	6500/4000/3000	21,000	257x152	1.77
DACO DISC GC209 CCT LED 200W	200W	200/150/100	6500/4000/3000	28,000	301x153	2.05

